

## Flooring Permit Affidavit

All commercial properties, including condominium units, are required to obtain a permit for flooring (tile, wood, marble). To obtain a permit for flooring, please provide the following documents to the permit counter.

- 1) Permit Application
- 2) Flooring Permit Affidavit
- 3) Two copies of the soundproofing manufacturer's literature with assembly value that complies with the Florida Building Code highlighted
- 4) Two sets of Floor Plans clearly indicating the area of work
- 5) Copy of a notarized Contract/Agreement between client and contractor may be requested

No review will be required for flooring permits **except for balcony/terraces, porches, bathrooms, lobbies and all other public commercial areas.**

**NOTE: A soundproofing inspection is mandatory in the City of Miami Beach**

### FLOORING PERMIT AFFIDAVIT

Process #: \_\_\_\_\_  
Address of Property: \_\_\_\_\_  
Product/Material: \_\_\_\_\_

I, \_\_\_\_\_, the qualifying agent # \_\_\_\_\_ for \_\_\_\_\_,  
(Name) (Contractor's License Number) (Company Name)

hereby certify that all requirements of the **Florida Building Code ( 6<sup>th</sup> Edition, 2017)**, Chapter 12, [Section 1207](#) – Sound Transmission, will be met at the above-mentioned location.

**Section 1207.2 - Air-borne sound:** Walls, partitions and floor/ceiling assemblies separating dwelling units and sleeping units from each other or from public or service areas shall have a sound transmission class of not less than 50, or not less than 45 if field tested, for air-borne noise when tested in accordance with ASTM E90. Penetrations or openings in construction assemblies for piping; electrical devices; recessed cabinets; bathtubs; soffits; or heating, ventilating or exhaust ducts shall be sealed, lined, insulated or otherwise treated to maintain the required ratings. This requirement shall not apply to entrance doors; however, such doors shall be tight fitting to the frame and sill.

**Section 1207.3 - Structure-borne sound:** Floor/ceiling assemblies between dwelling units and sleeping units or between a dwelling unit or sleeping unit and a public or service area within the structure shall have an impact insulation class rating of not less than 50, or not less than 45 if field tested, when tested in accordance with ASTM E492.

Signature: \_\_\_\_\_

Print Qualifier's Name: \_\_\_\_\_

State of \_\_\_\_\_, County of \_\_\_\_\_

Sworn to and subscribed before me this \_\_\_\_\_, Day of \_\_\_\_\_, 20\_\_\_\_\_

By \_\_\_\_\_

(SEAL) \_\_\_\_\_

Personally known or Produced Identification

Type of Identification \_\_\_\_\_